

j) Thickness of the scuff resistant coverings for the toe region;	3	4	5	6	7	8	9	10	11	12	13
	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3

- k) Outsole:
- i. Method of assembly of the outsole to the upper;
 - ii. Minimum thickness of the outsole (excluding cleats and heel);
 - iii. Cleat pattern (when used);

Injection

2.5mm for all sizes



- iv. Length of the outsole;

3	265.00mm
4	271.04mm
5	277.04mm
6	283.72mm
7	290.04mm
8	297.08mm
9	303.76mm
10	310.44mm
11	317.12mm
12	323.0mm
13	330.48mm

- v. Minimum cleat height (when used);

6.6mm for all sizes

- l) For outsoles that consist of more than one layer:

- i. Number of layers;
- ii. Material used in each layer;
- iii. Minimum thickness of each layer;
- iv. Method of assembly of the different layers to each other;
- i. Thickness of the penetration-resistant insert;
- ii. Method of assembly and layout of the penetration-resistant insert in the footwear;

2

PU/PU

4-6mm

Injection

N/A

N/A

Not applicable

- n) Heat and/or cold insulation (when fitted):

- i. Thickness of the heat and/or cold insulation;
- ii. Method of assembly of the heat and/or cold insulation to the footwear;
- i. Thickness of the metatarsal protective device;

Not applicable

Not applicable

Not applicable

- ii. Method of assembly of the metatarsal protective device to the footwear;

Not applicable

Not applicable

- p) Cut resistant layer (when fitted):

- iii. Thickness of the cut resistant layer;
- iv. Minimum height of the cut resistant layer above the feather edge;
- v. The minimum measurement of overlap of the cut resistant layer beyond the rear end of the toecap;
- vi. Method of assembly of the cut resistant layer to the footwear.

Not applicable

Not applicable

Not applicable

Not applicable